



Mystique (RL611)

Description

Mystique is a Laminate asphalt shingle made from a fibreglass mat and surfaced with mineral granules. Mystique is covered by a Limited Lifetime Warranty; its Standard Wind Warranty covers up to 180 km/h (110 mph) and its High Wind Warranty covers up to 220 km/h (135 mph) (as per special application instructions).

Usage

Mystique can be applied on roof slopes greater than 4/12. It can also be applied to roof slopes from 3/12 to 4/12 following special low slope application. Please refer to application instructions for further details.

Storage

Protect shingles from the weather. Do not store on the ground or in direct sunlight.

Building Products of Canada Corp.

9510, St. Patrick Street,
LaSalle (Quebec), Canada
H8R 1R9

www.bpcan.com

Physical Properties

Wind Warranty	180 km/h (110 mph) => Regular application 220 km/h (135 mph) => Special application
Weight (approx.)	36.4 kg (80 lb)
Coverage	3.1 m ² (33.3 ft ²)
Exposure	152 mm (6")
Dimensions	1016 mm x 356 mm (40" x 14")
Shingles/Bundle	20
Bundles/Pallet	36

Characteristics

Characteristics	Test Method	Requirement	BP Result
Tear strength (cross direction); g (N)	D-3462	1700 (16.7)	Pass
Tensile strength (machine direction); kN/m (lb/in)	D-146	10.5 (60)	Pass
Tensile strength (cross direction); kN/m (lb/in)	D-146	7 (40)	Pass
Fastener pull through at 0°C; N (lbf)	D-3462	186 (41.8)	Pass
Average net mass per unit area of finished shingles; g/m ² (lb/100 ft ²)	D-228	4394 (90)	Pass
Mass of glass mat per unit area; g/m ² (lb/100 ft ²)	D-228	85 (1.7)	Pass
Asphalt mass per unit area; g/m ² (lb/100 ft ²)	D-228	732 (15)	Pass

Applicable Standards

ASTM D-3018
ASTM D-3462-09
CSA A123.5M
UL 2390 Class H
UL 790, Class A Fire Resistance